

# AG Gases & Equipment Ltd

Unit 1A Britannic Works,

Broom Street, Hanley, Stoke-on-Trent,

England, ST1 2ER

Office: +44(0)1782616611 Email: prod@agequip.co.uk

www.agequip.co.uk



Customer PO

Cylinder NO

Part Code

Mfg Number

SDS Number

PO-005079

61894

112DACON-000800

AG-12311

AG1035

## Operating Instructions

- Do not handle the Cylinder or use the contents until you have read and understood the Safety Data Sheet.
- Ensure that the regulator is clean and compatible with the cylinder. Screw the regulator onto the valve outlet, point away from the body and other personnel until pressure is registered on the gauge (if fitted)
- Use on/off knob to release gas at pre-set flow rate indicated on the regulator.
- Always remove the regulator after use. This Cylinder will re-seal after the regulator is removed. There may be a slight "hiss" of gas as the regulator is removed.
- Use PPE as directed by the Safety Data Sheet.
- Please dispose of in accordance with local regulations.
- This cylinder can be recycled-please contact your local supplier for more details. these details always the same.

## Danger

- H220 - EXTREMELY FLAMMABLE GAS
- H280 - CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED
- H331 - TOXIC IF INHALED
- CGA-HG04 - MAY FORM EXPLOSIVE MIXTURES WITH AIR
- CGA-HG11 - SYMPTOMS MAY BE DELAYED
- CGA-HG16 - EXTENDED EXPOSURE TO GAS REDUCES THE ABILITY TO SMELL SULFIDES
- CGA-HG01 - MAY CAUSE FROSTBITE
- P202 - Do not handle until all safety precautions have been read and understood
- P210 - Keep away from Heat, Open flames, Sparks, Hot surfaces.  
- No smoking
- P260 - Do not breathe gas/vapors
- P271+P403 - Use and store only outdoors or in a well-ventilated place
- P280+P284 - Wear protective gloves, protective clothing, eye protection, respiratory protection

## Component

Carbon Monoxide

Nitrogen

UN1956 Compressed Gas n.o.s (carbon monoxide, nitrogen mixture)

## Requested Value

800ppm

Balance

## Certified Value

801ppm

Production Date:

Valid Date:

12-01-2029

Size: 112DA

Pressure: 70bar

Class: 2.2

